



三带通滤波片 (TRI-BANDPASS FILTERS)

Our ULTRA Series bandpass optical filters are designed with steep edges, high transmission, and up to OD10 blocking by design. They are ideal for fluorescence microscopy, flow cytometry, fluorescence imaging, and many other applications. Our standard OD4 bandpass filters are also available.

我们的ULTRA系列带通光学滤光片设计具有陡峭的边缘，高传输，高达OD10的阻塞设计。它们是荧光显微镜，流式细胞术，荧光成像和许多其他应用的理想选择。

滤光片型号 (Model)	中心波长 (nm)	半峰宽 (nm) FWHM	透射频带 Transmission Band	屏蔽等级 Blocking Level	直径尺寸 (mm)	滤光片厚度 (mm)	材质 (Substrate Type)	装配类型 Assembly Type	组装厚度 (mm)	价格
438-24_513-24_572-22 OD6 ULTRA Tri-Bandpass Filter	438 ±2.0 513 ±2.0 572 ±2.0	Band 1: 24 ±2.0 Band 2: 24 ±2.0 Band 3: 22 ±2.0	429-447nm >93% T Average, 504-522nm >93% T Average, 564-580nm >93% T Average	OD6: 300-417nm, 456nm, 458-493nm, 495nm, 530nm, 532-556nm, 589nm, 592-900nm; OD3: 900-1100nm	25	2.00	熔融石英 (Fused Silica)	阳极氧化铝环 (Anodized Aluminum Ring)	3.5	¥8,100.00
475-27_544-15_632-64 OD6 ULTRA Tri-Bandpass Filter	475 ±2.0 544 ±2.0 632 ±3.0	Band 1: 27 ±2.0 Band 2: 15 ±2.0 Band 3: 64 Nominal	465-485nm >93% T Average, 539-549nm >93% T Average, 603-661nm >93% T Average	OD6: 300-452nm 496-528nm 558-585nm 679-800nm	25	2.00	熔融石英 (Fused Silica)	阳极氧化铝环 (Anodized Aluminum Ring)	3.5	¥8,100.00
384-28_492.5-19_581-24 OD6 ULTRA Tri-Bandpass Filter	384 ±2.0 492.5 ±2.0 581 ±2.0	Band 1: 28 ±2.0 Band 2: 19 ±2.0 Band 3: 24 ±2.0	373-395nm >93% T Average, 486-499nm >93% T Average, 572-590nm >93% T Average	OD6: 300-362nm, 406-475nm, 476nm, 508nm, 510-559nm, 600nm, 602-900nm; OD3: 900-1100nm	25	2.00	熔融石英 (Fused Silica)	阳极氧化铝环 (Anodized Aluminum Ring)	3.5	¥8,100.00
457-29_530-27_628-36 OD6 ULTRA Tri-Bandpass Filter	457 ±2.0 530 ±2.0 628 ±3.0	Band 1: 29 ±2.0 Band 2: 27 ±2.0 Band 3: 36 Nominal	445-469nm >93% T Average, 519-541nm >93% T Average, 613-643nm >93% T Average	OD6: 300-436nm, 479-508nm, 553-598nm, 660-850nm; OD2: 250-300nm, 850-1100nm	25	2.00	熔融石英 (Fused Silica)	阳极氧化铝环 (Anodized Aluminum Ring)	3.5	¥8,100.00